



Transmig 350 Compact

TRANSMIG 350 COMPACT Industrial       **415**
V

SPECIFICATIONS	NUMBER OF OUTPUT VOLTAGE STEPS:	DUTY CYCLE TEST PERIOD:	WIRE SPOOL SIZE:
SUPPLY VOLTAGE:	32	5 & 10 minutes	300mm, 200mm or 100mm
380/415 volt	WELDING CURRENT RANGE:	WELDING ARC VOLTAGE RANGE:	PACKED WEIGHT:
3 phase 50/60Hz	25-350 amps	16-30V DC	107kg
SUPPLY PLUG & LEAD:	WIRE SPEED:	WIRE DIAMETER:	POWER SOURCE DIMENSIONS:
16 amps	1.0-20 m/min	Hard 0.6-1.2mm	H800mm x W355mm x D850mm
MINIMUM RECOMMENDED GENERATOR:	DUTY CYCLES:	Soft 0.9-1.2mm	PACKED DIMENSIONS:
16.5 kVA for maximum welding current	30% at 350 amps	Cored 0.8-1.2mm	H910mm x W365mm x D900mm

The Transmig 350 Compact is a multi-voltage, three phase, constant voltage DC power source ideally suited to medium fabrication, and heavier maintenance applications. The Transmig 350 provides excellent arc characteristics with gas metal arc welding (GMAW) or flux cored arc welding with or without gas (FCAW). The units are fitted with a new four roll drive system for improved feedability. These features together with an increased duty cycle of 350A @ 30%, make the unit the ideal choice for professional welding applications.

Features:

- ▲ 32 fine welding voltage control settings
- ▲ Multi-voltage supply capabilities
- ▲ Reverse polarity for gas/gasless welding
- ▲ Overload protection: thermostat warning light
- ▲ 4-roll wire drive system

Transmig 350 Compact Plant Contents:

Power Source, Genuine Tweco®4 MIG Gun (3.6M), Worklead (4M), Regulator/Flowmeter, Wheeling Kit/Cylinder Tray, Primary Lead for Factory Preset Supply Voltage, 1.0/1.2 Feed Rolls, Operating Manual

Ordering Information:

Transmig 350 Compact Part No. 706126

Feed Rolls:

Hard Wire:	0.6/0.8mm	7977229
	0.9/1.2mm	7977703
Soft Wire:	0.8/0.9mm	7977733
	1.0/1.2mm	7977730
Flux Cored:	0.8/0.9mm	7977734
	1.2/1.6mm	7977347



Part No. 706126

