



## TIG welding torch range

Welding craftsmen deserve the best tools. Kemppi TIG torches just feel that little bit better in the hand for those quality welding tasks.

Kemppi TIG torches suit a variety of equipment and are available from 4m to 16m in length.

Manufactured using the best materials, you can trust Kemppi TIG torches to perform, allowing you to concentrate on completing beautiful looking TIG welds.

## TIG welding torch options

**The TTM range** is equipped with manual gas valves to regulate the shielding gas flow, ensuring basic TIG welding tasks are easily completed. Use with MMA power sources for scratch and TouchArc TIG ignition.

**The TTK range** fits a wide range of industrial TIG welding machines. Standard thread terminations easily connect for power, gas and water (model dependent) and every model is fitted with an ignition switch, cable and plug as standard.

**The TTC range** is designed for use with specific Kemppi TIG machines and available in both gas and water cooled models. TTC torches support RTC10 and RTC20 remote control modules that replace the standard on/off switch with a convenient and precise remote current regulator for easy ignition and power control at distance.



	TTM 15 V	TTM 15 V BC	TTC 220 GV
Load capacity, DC-TIG	140 A (35%)	150 A (35%)	220 A (40%)
Machine connector	R $\frac{1}{4}$	R $\frac{3}{8}$	R $\frac{3}{8}$
Order code	6271432	627143201	627022304

# TIG Welding Torches



		TTC 130	TTC 130F	TTC 160	TTC 160S	TTC 220	TTC 200W	TTC 250W	TTC 250WS
Load capacity	DC 40 % ED	130 A	130 A	160 A	160 A	220 A	300 A	350 A	250 A
	DC 100 % ED						200 A	250 A	200 A
Electrodes	ø mm	1.0–2.4	1.0–2.4	1.0–2.4	1.0–2.4	1.0–3.2	1.0–2.4	1.0–4.0	1.0–4.0
Connection	Gas/current	R¼	R¼	R¼	R¼	R¼	R¼	R¼	R¼
	Liquid						Snap connection	Snap connection	Snap connection
Ordering code	4 m	627013004	627013104	627016004	627016204	627022004	627020504	627025504	627025704
	8 m	627013008	627013108	627016008	627016208	627022008	627020508	627025508	627025708
	16 m	627013016	627013116	627016016	627016216	627022016	627020516	627025516	627025716

RTC 10 (6185477) and RTC 20 (6185478) remote control units are available as options (see page 37).

		TTK 130	TTK 130F	TTK 160	TTK 160S	TTK 220	TTK 220S	TTK 300W	TTK 350W	TTK 250WS
Load capacity	DC 40 % ED	130 A	130 A	160 A	160 A	220 A	220 A	300 A	350 A	250 A
	DC 100 % ED							200 A	250 A	200 A
	AC 40 % ED	100 A	100 A	120 A	110 A	160 A	120 A	250 A	300 A	250 A
	AC 100 % ED							140 A	200 A	140 A
Electrodes	ø mm	1.0–2.4	1.0–2.4	1.0–2.4	1.0–2.4	1.0–3.2	1.0–3.2	1.0–2.4	1.0–4.0	1.0–4.0
Connection	Gas/current	R¼	R¼	R¼	R¼	R¼	R¼			
	Liquid/current							R¾	R¾	R¾
	Gas							R¼	R¼	R¼
Ordering code	4 m	627063004	627063104	627066004	627066204	627072004	627072304	627080504	627085504	627075704
	8 m	627063008	627063108	627066008	627066208	627072008	627072308	627080508	627085508	627075708
	16 m	627063016	627063116	627066016	627066216	627072016	627072316	627080516	627085516	627075716